



Heavy Duty Copper Tapping Connector

By Burndy
Catalog # [QPX2828](#)

VERSITAP™ Mechanical Parallel Clamp for
Copper/Copperweld; Accommodates: Run: #1 - 4/0 AWG; Tap:
#1 - 4/0 AWG



Application

For Tee, Cross, Parallel, Butt And Tap Connections, Copper,
Copperweld And Copperweld-Copper

General

Connector Type	Universal Clamp
EU RoHS Indicator	Yes
Installation Torque	240 LBS/in
Recommended in-lb	
Material	Copper
Material - Hardware	DURIUM™ Silicon Bronze
Physical Attribute - Screw Type	Hexagonal Bolt
Plated	N
Plating Type	Unplated
Sub Brand	VERSITAP
Trade Name	VERSITAP™
Type	QPX
UPC	781810342503

Dimensions

Dimension - Height fraction	2-3/8
Dimension - Height inch	2.38 in
Dimension - L Length Overall mm	46 mm
Dimension - Length Overall inch	1.81 in
Dimension - Width fraction	1-13/16 in
Dimension - Width inch	1.81 in
Dimension - Width mm	46 mm

Conductor Related

Conductor - Copper Str Run	1 AWG;1/0 ;2/0 AWG;3/0 AWG;4/0 AWG
Conductor - Copper Str Run Range	1 AWG-4/0 AWG
Conductor - Copper Str Tap	1 AWG;1/0 ;2/0 AWG;3/0 AWG;4/0 AWG
Conductor - Copper Str Tap Range	1 AWG-4/0 AWG
Conductor - CopperWeld Solid Run	9 AWG;8 AWG;7 AWG;6 AWG;5 AWG
Conductor - CopperWeld Solid Run Range	9 AWG-5 AWG
Conductor - CopperWeld Solid Tap	9 AWG;8 AWG;7 AWG;6 AWG;5 AWG
Conductor - CopperWeld Solid Tap Range	9 AWG-5 AWG
Conductor - CopperWeld Str Run	3 A AWG;3 J AWG;3 K AWG;3 N AWG;3 P AWG;2 A AWG;2 F AWG;2 G AWG;2 J AWG;2 K AWG;2 N AWG;2 P AWG;1 F AWG;1 G AWG;1 J AWG;1 K AWG;1 N AWG;1/0 F AWG;1/0 G AWG;1/0 J AWG;1/0 K AWG;2/0 F AWG;2/0 G AWG;2/0 J AWG;2/0 K AWG;2/0 V AWG;3/0 E AWG;3/0 EK AWG;3/0 F AWG;3/0 G AWG;3/0 J AWG;3/0 V AWG
Conductor - CopperWeld Str Run Range	3 A AWG-3/0 V AWG
Conductor - CopperWeld Str Tap	3 A AWG;3 J AWG;3 K AWG;3 N AWG;3 P AWG;2 A AWG;2 F AWG;2 G AWG;2 J AWG;2 K AWG;2 N AWG;2 P AWG;1 F AWG;1 G AWG;1 J AWG;1 K AWG;1 N AWG;1/0 F AWG;1/0 G AWG;1/0 J AWG;1/0 K AWG;2/0 F AWG;2/0 G AWG;2/0 J AWG;2/0 K AWG;2/0 V AWG;3/0 E AWG;3/0 EK AWG;3/0 F AWG;3/0 G AWG;3/0 J AWG;3/0 V AWG
Conductor - CopperWeld Str Tap Range	3 A AWG-3/0 V AWG
Conductor Type	• CU C Str-Run • CU Weld C Str-Run • CU Weld C Solid-Run

- CU C Str-Tap
- CU Weld C Str-Tap
- CU Weld C Solid-Tap

Certifications and Compliance

Certification - CSA Approved	Yes
Certification - UL Listed Direct Burial	No
Industry Standard(s)	UL486C
Standards - Industry Standards Met	UL486C
Standards - RoHS Compliance Status	EX
UL Listed	Yes

Logistics

Minimum Pack Quantity 1

Product Assets

- 3D Models - QPX2828_MODEL-IGES
- 3D Models - QPX2828_MODEL-PDF
- 3D Models - QPX2828_MODEL-STEP
- Catalogs - Full Line BURNDY Catalog
- Customer Notices - Prop 65 Notice
- Sales Drawings - sa007887-01



A proud member of the Hubbell Family.

©2024 Hubbell Incorporated. All rights reserved.
BRDY-QPX2828-SPEC-EN | REV 1/2024