

Roxtec SLF R sleeve

The Roxtec SLF R sleeve with flange is designed to cover imprecise openings and suitable with Roxtec R sealing solutions.

Attachment by bolting



SLF R 100 ALU



SLF R 100 PRIMED



SLF R 100 GALV



SLF R 100 AISI 316

Aluminum

Product	Internal Ø (mm)	External dimensions ØxZ (mm)	Aperture dimension Ø (mm)	Weight (kg)	Art. No
SLFR 70 ALU	71.5	160 x 55	87 - 93	0.33	5ASFR00008713
SLFR 75 ALU	76.5	165 x 55	93 - 99	0.4	5ASF000008712
SLFR 100 ALU	101	195 x 55	118 - 128	0.5	5ASFR00001917
SLFR 125 ALU	126	213 x 55	144 - 154	0.6	5ASF000004286
SLFR 127 ALU	128	213 x 55	144 - 154	0.6	5ASFR00008714
SLFR 150 ALU	151	236 x 55	168 - 178	0.7	5ASFR00007671
SLFR 200 ALU	201	290 x 55	218 - 228	1	5ASFR00001918

Galvanized mild steel

Product	Internal Ø (mm)	External dimensions ØxZ (mm)	Aperture dimension Ø (mm)	Weight (kg)	Art. No
SLFR 70 GALV	71.5	160 x 55	87 - 93	1.1	ASFR100700015
SLFR 75 GALV	76.5	165 x 55	93 - 99	1.2	ASFR100750015
SLFR 100 GALV	101	195 x 55	118 - 128	1.6	ASFR101000015
SLFR 125 GALV	126	213 x 55	144 - 154	1.9	ASFR101250015
SLFR 127 GALV	128	213 x 55	144 - 154	1.7	ASFR101270015
SLFR 150 GALV	151	236 x 55	168 - 178	2.2	ASFR101500015
SLFR 200 GALV	201	290 x 55	218 - 228	2.9	ASFR102000015

Primed mild steel

Product	Internal Ø (mm)	External dimensions ØxZ (mm)	Aperture dimension Ø (mm)	Weight (kg)	Art. No
SLFR 70 PRIMED	71.5	160 x 55	87 - 93	1	ASFR100700012
SLFR 75 PRIMED	76.5	165 x 55	93 - 99	1.2	ASFR100750012

Product	Internal Ø (mm)	External dimensions ØxZ (mm)	Aperture dimension Ø (mm)	Weight (kg)	Art. No
SLFR 100 PRIMED	101	195 x 55	118 - 128	1.6	ASFR101000012
SLFR 125 PRIMED	126	213 x 55	144 - 154	1.8	ASFR101250012
SLFR 127 PRIMED	128	213 x 55	144 - 154	1.7	ASFR101270012
SLFR 150 PRIMED	151	236 x 55	168 - 178	2.1	ASFR101500012
SLFR 200 PRIMED	201	290 x 55	218 - 228	2.8	ASFR102000012

Stainless steel

Product	Internal Ø (mm)	External dimensions ØxZ (mm)	Aperture dimension Ø (mm)	Weight (kg)	Art. No
SLFR 70 AISI316	71.5	160 x 55	87 - 93	1.1	5ASFR00002375
SLFR 75 AISI316	76.5	165 x 55	93 - 99	1.2	5ASFR00001785
SLFR 100 AISI316	101	195 x 55	118 - 128	1.8	5ASFR00001784
SLFR 125 AISI316	126	213 x 55	144 - 154	1.5	5ASFR00006186
SLFR 127 AISI316	128	213 x 55	144 - 154	1.7	5ASFR00003042
SLFR 150 AISI316	151	236 x 55	168 - 178	2.2	5ASFR00003264
SLFR 200 AISI316	201	290 x 55	218 - 228	2.6	5ASFR00006219